




LED MARKET

MIRACLE



FRONT




INDOOR LED PANEL


P 1.99mm

- Turn-key solution.
- Easy installation.
- Ground support compatible.
- Technical support available.
- 24 months warranty for all parts.
- USA based.
- In stock. Ships immediately.

BACK



FRONT SERVICEABLE



HIGH REFRESH RATE



HIGHER RESOLUTION



FIXED & RENTAL CABINETS



INDOOR PANEL



WALL MOUNTABLE



LED MARKET

MIRACKLE[®]

FRONT & BACK SERVICEABLE



WALL MOUNTABLE



HANGING BAR: FRONT



HANGING BAR: BACK



P 1.99mm

INDOOR LED PANEL




DIMENSIONS

FRONT SIZE

25,2 inches
64 cm


6,3 inches
16 cm



12,6 inches
32 cm


SIDE SIZE

3 inches
7,5 cm



VIEWING DISTANCE

4.9	<i>Pixel Pitch (mm)</i>	3.9	2.9	2.6	1.9	1.5	1.2	0.9
16 ft.	<i>Optimal Viewing Distance</i>	8 ft.	6 ft.	5.7 ft.	5 ft.	4 ft.	3 ft.	2 ft.



P 1.99mm

INDOOR LED PANEL



TECHNICAL SPECIFICATIONS

PIXEL PITCH	P1.99mm
LED ENCAPSULATION	King-Light SMD 1515
PIXEL DENSITY	320 x 240
SIZE	25.2" x 18.9" x 3" / 640 x 480 x 75mm
CHIP	IC2153
HIGH REFRESH RATE	3840hz
WEIGHT	21.6 lbs / 9.8 kg
RECEIVING CARD	NovaStar MRV-366

POWER SUPPLY

OPERATION POWER	100~240V 50-60Hz
MAX. POWER CONSUMPTION	200W/per panel
AVE. POWER CONSUMPTION	120W/per panel
CONNECTIONS POWER/DATA	Power-PowerCon In/Out; Data EtherCon In/Out

OPTICAL RATINGS

BRIGHTNESS	800 NITS
PROTECTION RATE	IP45
SCAN	1/40
FRAME FREQUENCY	60 Hz
VIEW ANGLE	Horizontal 160°/Vertical 160°
OPTIMAL VIEW DISTANCE	5 ft (1.5m)
BRIGHTNESS ADJUSTMENT	0~100% 100 Levels

P 1.99mm

INDOOR LED PANEL