




LED MARKET

Official Reseller  MIRACKLE

1.2 INDOOR IP45 MM





3-year warranty
for all parts.



US-Based
Company

INDOOR P1.25

LED SCREEN PANEL



INDOOR
LED PANEL



HIGH REFRESH
RATE



HIGHER
RESOLUTION



FIXED & RENTAL
CABINETS



FRONT
SERVICEABLE



WALL
MOUNTABLE

1.2MM

INDOOR
LED PANEL




HIGHLIGHTED COMPONENTS



1.2MM

INDOOR
LED PANEL



GOB MASK

- + Anti reflection
- + Anti Moire effect

GOB is an improvement of traditional SMD technology, it is used for certain applications that require high-level protection of the LED front module. Used for broadcasting and virtual studios.

[WATCH VIDEO](#)

TECHNICAL SPECIFICATIONS

PIXEL PITCH	1.2mm
LED ENCAPSULATION	King-Light SMD1010
PIXEL DENSITY	512 x 384
SIZE	640 x 480 x 75 mm / 25.2" x 18.9" x 3"
CHIP	ICN1065s
HIGH REFRESH RATE	3840hz
WEIGHT	22 lb / pc - 10 kg
RECEIVING CARD	NovaStar A8s-Pro



TURN-KEY SOLUTIONS

LED video walls packages in stock, ready to ship immediately across the USA.



EASY INSTALLATION

Connect the power cable, your HDMI device to the video processor and the ethernet port.



TECHNICAL SUPPORT


We have online support with video tutorials, software, user guides and specialized team.

1.2MM

INDOOR
LED PANEL



FRONT/BACK SERVICE



FRONT SERVICEABLE

Magnetic module system

Our magnetic module system is designed to simplify the assembly, repair, and replacement of LED display components. Each module is equipped with strong magnets, allowing for quick and tool-free installation. Modules can be easily removed manually or with a special tool, ensuring hassle-free maintenance and minimizing downtime.

POWER SUPPLY

Slim bar with noiseless technology.



RECEIVING CARD

A8s-Pro NovaStar 3840 Hz

By NovaStar, supports resolutions up to 512×384@60Hz. Supporting various functions, can significantly improve the display effect and user experience.




1.2MM

INDOOR
LED PANEL



PANEL DIMENSIONS




INSTALLATION METHODS



WALL MOUNT

The most stable option, secured through pre-drilled holes in Miracle® LED panels for reliable installation.



RIGGING

Modular structures with bar and ladder designs, offering height and flexibility configurations. Compatible with all Miracle® LED panels.



FREE STANDING

Durable aluminum construction, ideal for overhead truss systems, ceiling grids, cranes, or similar setups. Fully compatible with Miracle® LED panels.

[WATCH VIDEO](#)

1.2MM


INDOOR
LED PANEL



VIEWING DISTANCE

WATCH VIDEO

PIXEL PITCH (MM)	5.0	4.8	3.9	2.9	2.5	1.9	1.8	1.2
MIN. VIEW DISTANCE	25 FT.	20 FT.	15 FT.	10 FT.	6 FT.	5 FT.	4 FT.	3 FT.



OPTICAL RATINGS

BRIGHTNESS	1000 NITS
PROTECTION RATE	IP45
SCAN	1/64s
FRAME FREQUENCY	60 Hz
VIEW ANGLE	Horizontal 140°/Vertical 140°
MINIMUM VIEWING DISTANCE	3 ft (0.9 m)
BRIGHTNESS ADJUSTMENT	0~100% 100 Levels

POWER SUPPLY

OPERATION POWER	100~240V 50-60Hz
MAX. POWER CONSUMPTION	200W/per panel
AVE. POWER CONSUMPTION	120W/per panel
CONNECTIONS POWER/DATA	Power-PowerCon In/Out; Data EtherCon In/Out

1.2MM

INDOOR
LED PANEL



LED MARKET

Official Reseller  MIRACKLE



CONTACT US



WWW.LEDMARKETUSA.COM



INFO@LEDMARKETUSA.COM



2125 BISCAYNE BLVD, SUITE 272
MIAMI, FL, 33137



+1 (888) 204-8885



[LEDMARKETUSA](https://www.facebook.com/LEDMARKETUSA)



[LEDMARKETUSA](https://www.instagram.com/LEDMARKETUSA)



[LEDMARKETUSA](https://www.youtube.com/LEDMARKETUSA)